



Scan Modes:

Manual/Auto-sense



Communication: USB-KBW, USB-COM



Scan angle: Roll±360°, Pitch±50°, Skew±50°













Supermarket Retail

Restaurant

Parking lot

SPECIFICATIONS

Resolution	640 × 480 CMOS
Scan Modes	Manual /Auto-sense
Scanning Accuracy	≥5mil/0.127m (PCS90%, CODE39)
Size(L*W*H)	Scanner 150mm × 70mm × 95mm
CPU	32-bit
Decoding speed	25cm/s
Depth of field	10mm-500mm
Working Current	150mA
Working Temperature	20°C ~+ 50°C
Storage Temperature	-40°C ~+ 60°C
Angle of Scanning	Corner360°
Print Contrast Signal	≥25%
Angle of Pitch	Pitch ± 50°
Angle of Skew	Skew ± 50°
Weight	110g
Symbologies	1D: UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Standard 2 of 5(IATA25), Codabar (NW-7), etc. 2D: QR Code, Micro QR Code, Data Matrix, PDF417, etc.
Certifications	CE, FCC, ROHS





