

FEITIAN

P30 Desktop Printer



High-speed output



POS & PC & WiFi connection



Application & high compatibility



Multi-interface design



Intelligent connection



Retail



Supermarket



Restaurant



Hotel



Parking lot



Gas station

P30

SPECIFICATIONS

Printing Technology	Thermal line printing
Print Width	48-80±0.5mm
Effective Print Width	72mm
Print Density	576 points/line or 512 points/line
Print Speed	300mm/s
Print Interface	USB + LAN + RS232 USB+RS232 + BT (Optional) USB + RS232 + WIFI (Optional)
Media Dimensions	80mm: 79.5 ± 0.5 × 83mm 58mm: 57.5 ± 0.5 × 83mm
Thickness	0.06 -0.08 mm
Print Direction	Upward Paper Feeding or Forward Paper Feeding
Print Fonts	ANK, Font A: 1.5 × 3.0mm(12 × 24) Font B: 1.1 × 2.1mm(9 × 17) Simplified/Traditional: 3.0×3.0mm(24 × 24)
Barcode	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128
Cutters	AutomaticCutter: Half-Cut
Data Buffer	Input Buffering: 2048k bytes NV Flash: 256k bytes
Power Adapter	Input: AC100-240V, 50~60Hz Output: DC24V/2.5A Cash drawer output voltage: DC24V/1A
Operating Systems	Microsoft® Windows/Linux
Dimensions(Weight)	133 × 126 × 130mm/1.115 kg
Print Life	150KM
Working Environment	Temperature: 0°C~45°C
Storage Environment	Temperature: -10°C~60°C
Certifications	CE

